

Non-Slip Floor Cleaning Process

Area to be Cleaned		Frequency	Product Description	Method	Safety Information
Tiled Changing Room Floors			BONAMAIN	 CLEANING PROCESS 1) Dilute Bonamain with water at 1:5 1) Dilute Bonamain with water at 1:5 2) Apply to dry floor with a watering can fitted with a fine rose and sprinkle over evenly 	GLOVES
Shower/ Steam & Sauna Floor Tiles		6 Monthly or as required	Non-Slip Floor Cleaner	 3) Agitate/ scrub wet product over tile using the scrubber dryer or Rotowash machine. Allow product to soak into floor (lift vacuum attachment or collection tray to allow cleaning product to soak into the floor) 4) Continue to scrub over floor for 10-15 minutes 	COVERED FOOTWEAR
Poolside Tiles			For Ceramic Wet Foot Traffic Tiled Floors	 5) Collect soiled product by lowering the wet vacuum attachment or collection tray on the Rotowash machine 6) Hose/ rinse off with fresh water 7) Sign off floor cleaning check sheet 	WHEN DECANTING GLASSES GLOVES

For guidance and storage please refer to bottle label and product sheets

Bonasystems Limited

City House, Swallowdale Lane, Hemel Hempstead Industrial Estate,

Hemel Hempstead, Hertfordshire, HP2 7EA

Telephone 01442 419470 Fax 01442 419471

e-mail: info@bonasystems.com www.bonasystems.com

Nominated Distributor: