# Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Product name : Polish Cleaner

Product code : 103874E

Use of the : I

Substance/Mixture

Substance type:

: Metal polish

Mixture

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Stainless steel care. Spray and wipe manual process

Recommended restrictions

on use

: Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.

PO Box 11; Winnington Avenue

For professional users only.

Northwich, Cheshire, United Kingdom CW8 4DX

+ 44 (0)1606 74488 ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone : +441618841235

number +32-(0)3-575-5555 Trans-European

Poison Information Centre

telephone number

: For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 19.01.2023

Version : 4.0

# **Section: 2. HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222
	H229
Acute toxicity, Category 4	H332
Skin irritation, Category 2	H315
Eye irritation, Category 2	H319

103874E 1 / 13

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal Word : Danger

Extremely flammable aerosol. Hazard Statements : H222

> H229 Pressurized container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Harmful if inhaled. H332

**Precautionary Statements** : Prevention:

> Keep away from heat, hot surfaces, sparks, P210

> > open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition

source.

P251 Do not pierce or burn, even after use. P280

Wear protective gloves/ eye protection/ face

protection.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label: 2-butoxyethanol

## 2.3 Other hazards

None known.

# Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

## **Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01-2119457273-39	Aspiration hazard Category 1; H304	>= 30 - < 50
propane	74-98-6 200-827-9 01-2119486944-21	Note U Flammable gases Category 1; H220 Gases under pressure	>= 20 - < 25
2-butoxyethanol	111-76-2 203-905-0 01-2119475108-36	Acute toxicity Category 4; H302 Acute toxicity Category 3; H331 Skin irritation Category 2; H315 Eye irritation Category 2; H319	>= 10 - < 20

103874E 2/13

white mineral oil, petroleum	8042-47-5 232-455-8 01-2119487078-27	Aspiration hazard Category 1; H304	>= 10 - < 20

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Section: 4. FIRST AID MEASURES** 

#### 4.1 Description of first aid measures

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Get medical attention.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.

Use a mild soap if available. Get medical attention if irritation

develops and persists.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.

## 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### 4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

#### **Section: 5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: High volume water jet

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Fire Hazard

Keep away from heat and sources of ignition. Flash back possible over considerable distance.

Extremely flammable aerosol.

Pressurized container: May burst if heated.

Hazardous combustion

products

: Depending on combustion properties, decomposition products

may include following materials:

Carbon oxides

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment : Use personal protective equipment.

Further information : Use water spray to cool unopened containers. Fire residues and

contaminated fire extinguishing water must be disposed of in

103874E 3/13

accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

# **Section: 6. ACCIDENTAL RELEASE MEASURES**

## 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency

personnel

: Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in

sections 7 and 8.

Advice for emergency

responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

materials.

## 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

## 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to

do so.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information.

For personal protection see section 8.

See Section 13 for additional waste treatment information.

# Section: 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes. Do not breathe

dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which

might cause ignition of organic vapours). Contents under pressure. Do not puncture. Wash hands thoroughly after handling.

In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable

labeled containers.

Storage temperature : 0 °C to 40 °C

#### 7.3 Specific end uses

103874E 4 / 13

Specific use(s) : Stainless steel care. Spray and wipe manual process

# Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-N	0.	Value type (Form of exposure)	Control parameters	Basis
2-butoxyethanol	111-76	-2	TWA	25 ppm 123 mg/m3	UKCOSSTD
Further information				e skin. The assigned substances	
			STEL	50 ppm 246 mg/m3	UKCOSSTD
Further information	Sk Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
			TWA	20 ppm 98 mg/m3	2000/39/EC
Further information	skin	Identifies the possibility of significant uptake through the skin			
		Indicative			
			STEL	50 ppm 246 mg/m3	2000/39/EC
Further information	skin	Identifies the possibility of significant uptake through the skin			
		Indica	tive		

#### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

#### 8.2 Exposure controls

## Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

# Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

Eye/face protection (EN 166) : Safety glasses with side-shields

Hand protection (EN 374) : Recommended preventive skin protection

Gloves Nitrile rubber butyl-rubber

Breakthrough time: 1 – 4 hours

Minimum thickness for butyl-rubber 0.3 mm for nitrile rubber 0.2

mm or equivalent (please refer to the gloves

manufacturer/distributor for advise).

Gloves should be discarded and replaced if there is any indication

of degradation or chemical breakthrough.

103874E 5 / 13

Skin and body protection

(EN 14605)

: No special protective equipment required.

Respiratory protection (EN

143, 14387)

: When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:AX

## **Environmental exposure controls**

General advice : Consider the provision of containment around storage vessels.

## Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

**Appearance** : Aerosol. Colour colourless Odour : alcohol-like pΗ : 6.0 - 7.0, 100 %

Flash point : 76 °C closed cup

Odour Threshold : Not applicable and/or not determined for the mixture Melting point/freezing point : Not applicable and/or not determined for the mixture

Initial boiling point and

boiling range

: > 100 °C

Evaporation rate : Not applicable and/or not determined for the mixture Flammability (solid, gas) : Not applicable and/or not determined for the mixture Upper explosion limit Not applicable and/or not determined for the mixture Lower explosion limit : Not applicable and/or not determined for the mixture Vapour pressure Not applicable and/or not determined for the mixture Relative vapour density : Not applicable and/or not determined for the mixture

Relative density : 0.807 - 0.847 Water solubility : partly soluble

Solubility in other solvents : Not applicable and/or not determined for the mixture Partition coefficient: n-

: Not applicable and/or not determined for the mixture octanol/water

Auto-ignition temperature : Not applicable and/or not determined for the mixture Thermal decomposition : Not applicable and/or not determined for the mixture Viscosity, kinematic : Not applicable and/or not determined for the mixture Explosive properties : Not applicable and/or not determined for the mixture : The substance or mixture is not classified as oxidizing. Oxidizing properties

# 9.2 Other information

Not applicable and/or not determined for the mixture

103874E 6/13

# Section: 10. STABILITY AND REACTIVITY

## 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

#### 10.4 Conditions to avoid

Heat, flames and sparks.

## 10.5 Incompatible materials

None known.

## 10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials: Carbon oxides

## Section: 11. TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects

exposure

Information on likely routes of : Eye contact, Skin contact, Inhalation

Eye contact

Skin contact

## **Product**

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg

Acute inhalation toxicity : 4 h Acute toxicity estimate : > 20 mg/l

Test atmosphere: vapour

4 h Acute toxicity estimate: 2.63 mg/l

Test atmosphere: dust/mist

Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg

Skin corrosion/irritation : There is no data available for this product.

Serious eye damage/eye

irritation

: There is no data available for this product.

Respiratory or skin

sensitization

: There is no data available for this product.

103874E 7/13

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : 2-butoxyethanol LD50 rat: 1,500 mg/kg

white mineral oil, petroleum LD50 rat: > 5,000 mg/kg

**Potential Health Effects** 

Eyes : Causes serious eye irritation.

Skin : Causes skin irritation.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Harmful if inhaled.

Chronic Exposure : Health injuries are not known or expected under normal use.

**Experience with human exposure** 

Eye contact : Redness, Pain, Irritation

Skin contact : Redness, Irritation

Ingestion : No symptoms known or expected.

Inhalation : No information available.

## **Section: 12. ECOLOGICAL INFORMATION**

## 12.1 Toxicity

Environmental Effects : This product has no known ecotoxicological effects.

**Product** 

Toxicity to fish : no data available

Toxicity to daphnia and other : no data available

aquatic invertebrates

Toxicity to algae : no data available

Components

Toxicity to fish : 2-butoxyethanol96 h LC50 Fish: > 100 mg/l

103874E 8 / 13

white mineral oil, petroleum96 h LC50 Leuciscus idus (Golden

orfe): > 1,000 mg/l

Components

Toxicity to algae : 2-butoxyethanol72 h EC50 Aquatic Plant: 911 mg/l

## 12.2 Persistence and degradability

#### **Product**

no data available

#### Components

Biodegradability : propaneResult: Readily biodegradable.

2-butoxyethanolResult: Readily biodegradable.

white mineral oil, petroleumResult: Biodegradable

## 12.3 Bioaccumulative potential

no data available

# 12.4 Mobility in soil

no data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product**

Assessment : This substance/mixture contains no components considered to be

either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or

higher.

## 12.6 Other adverse effects

no data available

#### Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

#### 13.1 Waste treatment methods

Product : Where possible recycling is preferred to disposal or incineration. If

recycling is not practicable, dispose of contents/container in accordance with local regulations Dispose of wastes in an

approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken

to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local,

state, and federal regulations.

103874E 9 / 13

Guidance for Waste Code selection

: Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

# **Section: 14. TRANSPORT INFORMATION**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 1950

14.2 UN proper shipping : AEROSOLS

name

14.3 Transport hazard : 2

class(es)

14.5 Environmental hazards : No 14.6 Special precautions for : None

user

Air transport (IATA)

: 1950 14.1 UN number

14.2 UN proper shipping : Aerosols, flammable

name

14.3 Transport hazard : 2.1

class(es)

14.5 Environmental hazards : No 14.6 Special precautions for : None

user

Sea transport (IMDG/IMO)

: 1950 14.1 UN number

: AEROSOLS 14.2 UN proper shipping

name

14.3 Transport hazard : 2.1

class(es)

14.5 Environmental hazards : No 14.6 Special precautions for : None

user

14.7 Transport in bulk : Not applicable.

according to Annex II of MARPOL 73/78 and the IBC

dangerous substances.

Code

# **Section: 15. REGULATORY INFORMATION**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso III: Directive FLAMMABLE AEROSOLS P3a 2012/18/EU of the European Lower tier: 150 t

Parliament and of the Council Upper tier: 500 t on the control of majoraccident hazards involving

103874E 10/13

## **National Regulations**

# Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)

Regulations.

The Control of Substances Hazardous to Health Regulations.

Health and Safety at Work Act.

#### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

## **Section: 16. OTHER INFORMATION**

#### Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Aerosols 1, H222	Based on product data or assessment
Acute toxicity 4, H332	Calculation method
Skin irritation 2, H315	Calculation method
Eye irritation 2, H319	Calculation method

#### **Full text of H-Statements**

H220	Extremely flammable gas.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.

#### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways, ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk, IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical

103874E 11 / 13

Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand, 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

## **Annex: Exposure Scenarios**

## Exposure Scenario: Stainless steel care. Spray and wipe manual process

Life Cycle Stage : Widespread use by professional workers

Product category PC31 Polishes and wax blends

## Contributing scenario controlling environmental exposure for:

Environmental release : ERC8a Wide dispersive indoor use of processing aids in open

category systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment : Municipal sewage treatment plant

Plant

# Contributing scenario controlling worker exposure for:

: PROC10 Process category Roller application or brushing

Exposure duration : 480 min

Operational conditions and

: Indoor

risk management measures

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

103874E 12 / 13

Skin Protection : see section 8

Respiratory Protection : see section 8

# Contributing scenario controlling worker exposure for:

Process category : PROC11 Non industrial spraying

Exposure duration : 60 min

Operational conditions and

risk management measures

: Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

103874E 13 / 13