

Sirafan Speed**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Sirafan Speed

Product code : 110660E

Use of the
Substance/Mixture : Disinfectant

Substance type: : Mixture

Product dilution information : No dilution information provided.



1.2 Relevant identified uses of the substance or mixture and uses advised againstIdentified uses : Surface disinfectant. Manual process
Disinfection product. Semi-automatic processRecommended restrictions
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com**1.4 Emergency telephone number**Emergency telephone
number : +441618841235
+32-(0)3-575-5555 Trans-EuropeanDate of Compilation/Revision : 26.01.2022
version : 1.12**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3	H226
Eye irritation, Category 2	H319
Specific target organ toxicity - single exposure, Category 3, Central Nervous System	H336

The classification of this product is based on toxicological assessment.

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)**

Sirafan Speed

Hazard pictograms	:		
Signal Word	:	Warning	
Hazard Statements	:	H226 H319 H336	Flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary Statements	:	Prevention: P210 P280e	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear eye protection/face protection.

Hazardous components which must be listed on the label:
Isopropyl Alcohol
propan-1-ol

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Isopropyl Alcohol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 30 - < 50
propan-1-ol	71-23-8 200-746-9 01-2119486761-29	Flammable liquids Category 2; H225 Serious eye damage Category 1; H318 Specific target organ toxicity - single exposure Category 3; H336	>= 20 - < 25
Substances with a workplace exposure limit :			
Propylene glycol	57-55-6 200-338-0 01-2119456809-23	Not Classified;	>= 1 - < 2.5

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

Sirafan Speed

- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Fire Hazard
Keep away from heat and sources of ignition.
Flash back possible over considerable distance.
Beware of vapours accumulating to form explosive concentrations.
Vapours can accumulate in low areas.
- Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides

5.3 Advice for firefighters

- Special protective equipment for firefighters : Use personal protective equipment.
- Further information : Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

- Advice for non-emergency personnel : Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Sirafan Speed

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. Open drum carefully as content may be under pressure. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 25 °C

7.3 Specific end uses

Specific use(s) : Surface disinfectant. Manual process
Disinfection product. Semi-automatic process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Sirafan Speed

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Isopropyl Alcohol	67-63-0	TWA	400 ppm 999 mg/m3	UKCOSSTD
		STEL	500 ppm 1,250 mg/m3	UKCOSSTD
propan-1-ol	71-23-8	STEL	250 ppm 625 mg/m3	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	200 ppm 500 mg/m3	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
Propylene glycol	57-55-6	TWA (particles)	10 mg/m3	UKCOSSTD
		TWA (Total vapour and particles)	150 ppm 474 mg/m3	UKCOSSTD

DNEL

Isopropyl Alcohol	:	<p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 888 mg/cm2</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m3</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 319 mg/cm2</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m3</p> <p>End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 26 ppm</p>
Propylene glycol	:	<p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 168 mg/m3</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 50 mg/m3</p>

Sirafan Speed

	<p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m³</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 213 mg/cm²</p> <p>End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 85 ppm</p>
--	---

PNEC

<p>Isopropyl Alcohol</p>	<p>: Fresh water Value: 140.9 mg/l</p> <p>Marine water Value: 140.9 mg/l</p> <p>Intermittent use/release Value: 140.9 mg/l</p> <p>Fresh water Value: 552 mg/kg</p> <p>Marine sediment Value: 552 mg/kg</p> <p>Soil Value: 28 mg/kg</p> <p>Sewage treatment plant Value: 2251 mg/l</p> <p>Oral Value: 160 mg/kg</p>
<p>Propylene glycol</p>	<p>: Fresh water Value: 260 mg/l</p> <p>Marine water Value: 26 mg/l</p> <p>Intermittent use/release Value: 183 mg/l</p> <p>Fresh water sediment Value: 572 mg/kg</p> <p>Marine sediment Value: 57.2 mg/kg</p>

Sirafan Speed

	Sewage treatment plant Value: 20000 mg/l Soil Value: 50 mg/kg
--	--

8.2 Exposure controls

Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

Eye/face protection (EN 166) : Safety glasses with side-shields

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : colourless
- Odour : alcohol-like
- pH : 7.5 - 8.5, 100 %
- Flash point : 25 °C closed cup
- Odour Threshold : Not applicable and/or not determined for the mixture
- Melting point/freezing point : Not applicable and/or not determined for the mixture
- Initial boiling point and boiling range : Not applicable and/or not determined for the mixture
- Evaporation rate : Not applicable and/or not determined for the mixture
- Flammability (solid, gas) : Not applicable and/or not determined for the mixture

Sirafan Speed

Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 0.876 - 0.896
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:
Carbon oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of : Inhalation, Eye contact, Skin contact

Sirafan Speed

exposure

Product

- Acute oral toxicity : There is no data available for this product.
- Acute inhalation toxicity : There is no data available for this product.
- Acute dermal toxicity : There is no data available for this product.
- Skin corrosion/irritation : No skin irritation
- Serious eye damage/eye irritation : Eye irritation
Method: OECD Test Guideline 405
Test substance: Similar Product
- Respiratory or skin sensitization : There is no data available for this product.
- Carcinogenicity : There is no data available for this product.
- Reproductive effects : There is no data available for this product.
- Germ cell mutagenicity : There is no data available for this product.
- Teratogenicity : There is no data available for this product.
- STOT - single exposure : May cause drowsiness or dizziness.
- STOT - repeated exposure : There is no data available for this product.
- Aspiration toxicity : There is no data available for this product.

Components

- Acute oral toxicity : Isopropyl Alcohol LD50 rat: 5,840 mg/kg
propan-1-ol LD50 : 1,870 mg/kg
Propylene glycol LD50 rat: 22,000 mg/kg

Components

- Acute inhalation toxicity : Isopropyl Alcohol 4 h LC50 rat: > 30 mg/l
Test atmosphere: vapour

propan-1-ol 4 h LC50 : 26.76 mg/l
Test atmosphere: dust/mist

Propylene glycol 4 h LC50 rabbit: 158.5 mg/l
Test atmosphere: dust/mist

Components

- Acute dermal toxicity : Isopropyl Alcohol LD50 rabbit: 12,870 mg/kg
propan-1-ol LD50 : 4,032 mg/kg

Potential Health Effects

Sirafan Speed

- Eyes : Causes serious eye irritation.
- Skin : Health injuries are not known or expected under normal use.
- Ingestion : Health injuries are not known or expected under normal use.
- Inhalation : Inhalation may cause central nervous system effects.
- Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

- Eye contact : Redness, Pain, Irritation
- Skin contact : No symptoms known or expected.
- Ingestion : No symptoms known or expected.
- Inhalation : Dizziness, Drowsiness

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

- Environmental Effects : This product has no known ecotoxicological effects.

Product

- Toxicity to fish : no data available
- Toxicity to daphnia and other aquatic invertebrates : no data available
- Toxicity to algae : no data available

Components

- Toxicity to fish : Isopropyl Alcohol 96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l
- propan-1-ol 96 h EC50: 3,800 mg/l
- Propylene glycol 96 h LC50 Fish: > 10,000 mg/l

Components

- Toxicity to daphnia and other aquatic invertebrates : Isopropyl Alcohol LC50 Daphnia magna (Water flea): > 10,000 mg/l
- propan-1-ol 48 h LC50: 1,000 mg/l
- Propylene glycol 48 h EC50 Aquatic Invertebrate: 18,340 mg/l

Components

- Toxicity to algae : propan-1-ol 48 h EC50: 9,170 mg/l

12.2 Persistence and degradability

Product

Sirafan Speed

no data available

Components

Biodegradability : Isopropyl AlcoholResult: Readily biodegradable.
propan-1-olResult: Readily biodegradable.
Propylene glycolResult: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Section: 14. TRANSPORT INFORMATION

Sirafan Speed

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 1987
14.2 UN proper shipping name : ALCOHOLS, N.O.S.
(Isopropanol, Propanol)
14.3 Transport hazard class(es) : 3
14.4 Packing group : III
14.5 Environmental hazards : No
14.6 Special precautions for user : None

Air transport (IATA)

14.1 UN number : 1987
14.2 UN proper shipping name : Alcohols, n.o.s.
(Isopropanol, Propanol)
14.3 Transport hazard class(es) : 3
14.4 Packing group : III
14.5 Environmental hazards : No
14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

14.1 UN number : 1987
14.2 UN proper shipping name : ALCOHOLS, N.O.S.
(Isopropanol, Propanol)
14.3 Transport hazard class(es) : 3
14.4 Packing group : III
14.5 Environmental hazards : No
14.6 Special precautions for user : None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Seveso III: Directive : FLAMMABLE LIQUIDS P5c
2012/18/EU of the European Parliament and of the Council : Lower tier : 5,000 t
on the control of major- Upper tier : 50,000 t
accident hazards involving dangerous substances.

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)

Sirafan Speed

Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Flammable liquids 3, H226	Based on product data or assessment
Eye irritation 2, H319	Based on product data or assessment
Specific target organ toxicity - single exposure 3, H336	Based on product data or assessment

Full text of H-Statements

H225 Highly flammable liquid and vapour.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Sirafan Speed

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.