



Product Code: HR150G

Refrigerated Undercounter Cabinet with Glass Door (no light)



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate in ambient up to 25°C (ISO Climate Class 3)
- Supplied with glass door.

Shelving		Base Fittings		Doors	
Nylon Coated Shelf	Option	Castors - Rear Fixed	Standard	Glass	Standard
Refrigeration		Levelling Bolts	Standard	Specification	
R134a - Industry Standard	Standard	Electrical & Service Data		Refrigerator +3/+5°C	Standard
R600a	Option	230/50/1	Standard	Width (mm)	605
Integral Refrigeration System	Standard	Fuse Required (A)	10	Depth (mm)	640
Finish				Height (mm)	830
s/s ext & alu int	Standard			Gross Volume (Ltr)	150
				Noise dBA @ 1m	68.8

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for ventilation, ensure that 50mm clearance is allowed above and around the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet

Energy Performance Data and information



Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
Phone 08432 168800 | Email sales@foster-uk.com | Visit www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.